A dedicated range of products for wine labelling

Issued:
TECHNICAL DATA SHEET *(provisional)* 09.09.2011

Code:

Product: **FELT OAK WHITE K8w WP5** **2510 K8w WP5**

Face Material: **FELT OAK WHITE**

White felt marked, fine natural wine paper

Wet strength and antimould treated

Basis Weigth: 90 g/m² (ISO 536) Thickness: 118 µm (ISO 534)

Adhesive: **WP5**

Special permanent acrylic adhesive, specific for labelling of glass wine bottles. Provide good adhesion on sligthly damp and cold glass.
Complies with the rules and recommendations of BfR (BgVV).

Loop-tack (FTM9 on glass): > 9 N
Peel-adhesion (FTM2 on glass) : > 11 N/25mm

Minimum Application Temperature: > 5°C
Service Temperature: - 25°C to + 75°C

Liner: **K8w**

White supercalandered glassine paper, with good die-cutting and labeling properties.
Especially suitable for embossing processes.

Basis Weigth: 80 g/m² (ISO 536) Thickness: 71 µm (ISO 534)
Transparency: > 39% (DIN 53147)

Note: Good performance during immersion in ice-buckets. Testing is recommended.
Shelf-life: 18 months when stored at 22°C and 55% RH

WARRANTY:
INTERCOAT materials are manufactured according to highest quality standards and pass stringent quality controls prior to despatch. Any material showing an evident defect of manufacturing will be replaced promptly without charge. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advise or technical support the INTERCOAT technical department will be pleased to assist.

AMC Pancke AG - **Division INTERCOAT** - Boschstrasse 12, D-24568 Kaltenkirchen
Tel. 0049 (0) 4191 8005 0 - Fax 0049 (0) 4191 2450
info@intercoat.de - www.winelabelsupporters.com